



FAST FLOW PUMPS

3" Aluminum Single Motor Pump

Fast Facts

- 28lb / 13kg
- 550GPM / 2081LPM Water Flow
- 300Ft / 92m Vertical Head
- 1500 - 3000PSI / 103-206 Bar
- 5 - 20 GPM / 18 - 75 LPM Hydraulic Flow
- 3" Male Camlock
- 16" x 10" x 12" / 41 cm x 25 cm x 30 cm
- AW-32 or AW-46 Hydraulic Fluid



For Water & Clear Fluids Only

3" ALUMINUM
SINGLE MOTOR PUMP

More Information

Features

- Very High Flow Rates
- High Vertical Head Pressure
- Self Priming
- Variable Speed & Flow
- Small Portable Size
- Corrosion Resistant Aluminum
- NO Mechanical Seals
- NO Internal Friction
- Low Maintenance Design
- Explosion-Proof
- Not for Solids Pumping
- CE Certified

Competitive Advantages

- Lightweight and Portable at 28 LBS (12kg)
- Single person can lift and position
- Corrosion resistant aluminum for long life
- Cost effective compared to other pumps
- Simple design allows for easy servicing
- Field service in under an hour
- Replacement parts shipped anywhere



Fast Flow's patented double suction technology produces superior flow rates and high head pressures. It is the only line of submersible pumps with no mechanical seals or internal friction. The high-efficiency hydraulic motor has several advantages over electric submersibles.

Applications



- Water transfer
- Dewatering
- Diesel and jet fuel
- Wash down pumping
- Limited Access
- Irrigation aeration
- Disaster response
- Waste pumping
- Salvage jetting

