



FAST FLOW PUMPS

3" Ductile Iron Twin Agitator Pump

Fast Facts

- 72lb / 32.6kg
- 600GPM / 2271LPM Water Flow
- 350ft / 106m Vertical Head
- 2250-3300PSI / 155-227 Bar
- 8-21 GPM / 30-79 LPM Hydraulic Flow
- 3" Male Camlock
- 29" x 10" x 12" / 73cm x 25cm x 30cm
- AW-32 or AW-46 Hydraulic Fluid



3" DUCTILE IRON
TWIN AGITATOR PUMP

More Information

Features

- Designed for Severe Service
- NO Mechanical Seals
- NO Shaft Bearings
- NO Internal Friction
- Run Dry Technology
- Very High Flow Rates
- High Vertical Head Pressure
- Self Priming
- Variable Speed & Flow
- Small Portable Size
- Slurry and Solids Pumping
- Effective Small Dredge Pump

Competitive Advantages

- Handles abrasive solids pumping applications
- Pump 20 pound per gallon oilfield slurries
- Durable ductile iron for long life
- Field service in under an hour
- Features top lifting ring and debris cage
- Twin hydraulic motors self lubricate



Fast Flow's Twin Agitators are engineered to keep your toughest pumping applications moving. Designed to mount directly onto Fast Flow's twin motor pumps, these dual agitators break up settled solids, fluidize heavy sludges, and ensure consistent suction—no matter how thick or abrasive the material. Ideal for dredging, industrial waste pits, frac tanks, and anywhere sediment buildup threatens flow.

Applications



- Construction dewatering
- Floodwater abatement
- Utility break locations
- Vessel dewatering
- Water pumping
- Small dredging jobs

