



FAST FLOW PUMPS

3" Ductile Iron Twin Motor Pump

Fast Facts

- 70lb / 32kg
- 600GPM / 2271LPM Water Flow
- 350ft / 106m Vertical Head
- 2250-3300 PSI / 155-227 Bar
- 8-21 GPM / 30-79 LPM
- 3" Male Camlock
- 29" x 10" x 12" / 73cm x 25cm x 30cm
- AW-32 or AW-46 Hydraulic Fluid



3" DUCTILE IRON
TWIN MOTOR PUMP

More Information

Features

- Very High Flow Rates
- High Vertical Head Pressure
- Self Priming
- Run Dry Technology
- Variable Speed & Flow
- Small Portable Size
- Heavy Solids Pump
- Fits in Manhole
- NO Internal Friction
- NO Mechanical Seals
- NO Shaft Bearings

Competitive Advantages

- Designed for severe service applications
- Handles abrasive solids pumping applications
- Pump 20lb (9kg) per gallon (3L) oilfield slurries
- Anti-clog twin motor, double suction technology
- Durable ductile iron for long life
- Optional high strength twin agitators available
- Twin hydraulic motors self lubricate



The Fast Flow 3" Ductile Iron Twin Motor Pump delivers serious hydraulic performance in a small footprint. Designed for high-head and high-flow applications, this twin motor pump offers the torque and reliability needed for demanding jobs. Built with a heavy-duty ductile iron housing and dual hydraulic motors, it's ideal for abrasive, corrosive, or debris-laden fluids.

Applications



- Fly ash pumping
- Pit dewatering
- Directional drilling
- Construction dewatering
- Floodwater abatement
- Utility break locations

