



FAST FLOW PUMPS

60HP Electric Hydraulic Unit

Fast Facts

- 60HP / 45kw
- 1000-5000PSI / 172-345 Bar
- Up to 30GPM (113LPM) Hydraulic Flow
- 55 Gallon (208Liter) Hydraulic Tank
- 3 Phase 230V/480V Electrical
- Weighs 3800lbs (1723kg)
- 84" x 57" x 55" (213cm x 145cm x 139cm)
- 32 or 46 AW, BIO, NS Hydraulic Fluid



60HP ELECTRIC HYDRAULIC POWER UNIT

FEATURES

Motor

- TEFC 1800RPM 3 Phase Motor
- 1.25 service factor - continuous duty rated
- Cast iron frame with built in grease fitting
- Up to 5year manufacturer motor warranty
- Motor phase loss and over temperature protection
- Nema 3R or 4
- Soft starter and combination breaker available

Hydraulics

- Custom hydraulics, flow, and pressure
- Low level hydraulic shutdown available
- High capacity hydraulic oil cooler available
- Hydraulic oil filter with spin on cartridge
- Variable flow hydraulic controls available
- 5000 PSI hydraulic gauges
- Hydraulic oil level & temperature indicators

Safety

- Starter wired to motor
- Start / stop
- System hydraulic relief protection
- Easy to read safety labeling
- Adjustable amperage FLA motor protection
- Full System Test at Factory

Available Options

- Fully custom hydraulic circuits, pressures, and flow
- 208-230 Volt / 460 Volt /575 Volt power options
- Control power transformer for control electronics
- Control panel push button and HOA options
- 100% Oil Spill Containment
- Top & fan Safety Grating
- Certified 4 point lift pad
- 10" forklift boots & low point drain plugs

Power that's clean, quiet, and consistently reliable. The 60HP Electric Hydraulic Power Unit delivers high-efficiency performance in a compact, user-friendly package—ideal for indoor, offshore, and environmentally sensitive applications. With zero exhaust emissions and reduced noise output, this unit offers all the strength of a 60-horsepower hydraulic system while meeting strict operational and environmental requirements.

Hydraulic Capabilities

69GPM	1500PSI
51GPM	2000PSI
34GPM	3000PSI
26GPM	4000PSI
21GPM	5000PSI

