



FAST FLOW PUMPS

25HP Diesel Hydraulic Unit

Fast Facts

- 25HP / 18kW
- 2250-5000PSI / 155-345 Bar
- Up to 17GPM (64LPM) Hydraulic Flow
- 14 Gallon (52 Liter) Hydraulic Tank
- 14 Gallon (52 Liter) Diesel Tank
- Weights 1350lbs (612kg)
- 51" x 26" x 40" (130 cm x 66 cm x 102 cm)
- 32 or 46 AW, BIO, NS Hydraulic Fluid



25HP DIESEL
HYDRAULIC POWER UNIT

FEATURES

Engine

- Tier 4 Final Yanmar Engine
- Electric start with battery
- Rubber engine vibration dampers
- Engine safety shutdown package
- Fixed speed engine
- EPA rated engine
- Engine has max RPM of 3600.

Hydraulics

- Single circuit variable flow hydraulic controls
- Low level hydraulic fluid shutdown
- High capacity hydraulic cooling system
- Hydraulic oil filter with spin on cartridge
- 3/4" or 1" quick disconnect couplings
- 5000 PSI hydraulic gauges
- Screw together supply and return fittings
- High performance variable displacement
- Efficient piston pump hydraulics

Safety

- Hydraulic unit enclosure to protect against sun and elements
- 14 Gallon fuel tank with level indicator
- Hydraulic system adjustable relief valve
- Oil spill drip pan
- Easy to read operation labeling
- Hydraulic oil level & temperature indicators

Available Options

- Key switch and engine hour meter
- Powder coated frame
- Center Point Lift
- Sub base fuel tank
- Removable fuel and hydraulic tanks
- Variable hydraulic pressure valve with adjustable relief
- Easily fits in the bed of a half ton truck
- Fuel and hydraulic filtration
- Low Level hydraulic shutdown protection

Compact power meets rugged performance with our 25HP Diesel Hydraulic Power Unit, designed for field operations where mobility, durability, and efficiency matter most. Weighing less than comparable units in its class, this portable hydraulic power pack is ideal for contractors, mobile technicians, and remote job sites where every pound and inch of space counts.

Hydraulic Capabilities

20GPM	1500PSI
15GPM	2000PSI
12GPM	2500PSI
10GPM	3000PSI
8GPM	4000PSI
6GPM	5000PSI

