



FAST FLOW PUMPS

203HP Diesel Hydraulic Unit

Fast Facts

- 203HP / 151kw
- 1000-5000PSI / 172-345 Bar
- Up to 99GPM Hyd. Flow at 3000PSI
- 106 Gallon (401 Liter) Hydraulic Tank
- 106 Gallon (401 Liter) Diesel Tank
- Weights 8500lbs (3401kg)
- 120" x 68" x 78" (304 cm x 172 cm x 198 cm)
- PowerFlowNZ-32 is Standard, Other Fluids available on request



203HP DIESEL HYDRAULIC POWER UNIT

FEATURES

Engine

- Isuzu 4HK Engine
- Engine Monitoring System
- Engine Safety Shutdown Package
- Double Fuel and Hydraulic Filtration
- Air Inlet Emergency Shutdown Valve
- Electric Start with Battery & Weather Safe Battery Box

Hydraulics

- Twin or Single Circuit Hydraulic Flow Controls
- Low Level Hydraulic Fluid Shutdown
- Best in Class 12 Volt Dual Fan Hydraulic Cooling Unit
- Twin Element Hydraulic Oil Filter with Spin On Cartridges
- 100% Oil Spill and Fuel Spill Containment
- 5000PSI Hydraulic Gauges
- Various Hydraulic Disconnect Options Available
- Hydraulic Oil Level & Temperature Indicators

Safety

- Safety Transport Tie Down Eye Pads
- DOT Registered and Approved for Highway Towing
- Variable Pressure Hydraulic Relief Valve
- Heavy Duty Center Point Lift
- Easy to Read Safety and Operation Labeling
- Flame Arrestor Exhaust with Heat Shield and Rain Cap
- 10 Ply Trailer Tires

Designed for heavy-duty industrial, marine, and municipal applications, our robust 203HP Hydraulic Power Unit is engineered to maximize efficiency and performance. Built to withstand extreme conditions, this HPU provides dependable hydraulic flow for demanding tasks, including:

- Dredging
- Drilling
- Dewatering
- Pile driving
- Operation of hydraulic submersible pumps

FOR ADDITIONAL SYSTEM OPTIONS CONTACT US:

228.475.2468

sales@fastflowpumps.com

Continuous Hydraulic Capabilities

99GPM	3000PSI
74GPM	4000PSI
59GPM	5000PSI

