



FAST FLOW PUMPS

48HP Diesel Hydraulic Unit

Fast Facts

- 48HP / 36kw
- 1000-3000PSI / 172-206 Bar
- Up to 22GPM Hyd. Flow at 3000PSI
- 18 Gallon (68 Liter) Hydraulic Tank
- 40 Gallon (151 Liter) Diesel Tank
- Weights 3900lbs (1770kg)
- 73" x 48" x 61" (185cm x 122cm x 155cm)
- 32 or 46 AW, BIO, NS Hydraulic Fluid



48HP DIESEL HYDRAULIC POWER UNIT

FEATURES

Engine

- Tier 4 Final Deutz Engine
- 100% duty cycle
- Engine safety shutdown package
- Rubber engine vibration dampers
- Electric start with battery
- Weather safe battery box

Hydraulics

- Single circuit variable flow hydraulic controls
- High capacity hydraulic cooling system
- Hydraulic oil filter with spin on cartridge
- 3/4" or 1" quick disconnect couplings
- 5000 PSI hydraulic gauges
- Screw together supply and return QD fittings
- Load sense pressure compensated piston pump

Safety

- 18 Gallon fuel tank with level indicator
- Hydraulic system adjustable relief valve
- Hydraulic Isolation Valve
- Easy to read operation & safety labeling
- Hydraulic oil level & temperature indicators

FOR ADDITIONAL SYSTEM OPTIONS CONTACT US:

228.475.2468

sales@fastflowpumps.com

Count on dependable power—no matter where the job leads you. The 48HP Diesel Hydraulic Power Unit strikes an excellent balance between fuel efficiency and rugged durability, making it an ideal choice for challenging field conditions.

Designed within a compact and maneuverable frame, this unit ensures easy transport and rapid setup while delivering the robust hydraulic output you expect from a 48-horsepower diesel system. Whether you're managing demanding construction projects or maintaining remote infrastructure, this power unit is crafted to fulfill your requirements.

Hydraulic Capabilities

35GPM	2000PSI
26GPM	2500PSI
22GPM	3000PSI

