



# FAST FLOW PUMPS

## 4" Ductile Iron Twin Agitator Pump

### Fast Facts

- 208 lbs / 90.7 kg
- 1200 GPM / 4542.5LPM Water Flow
- 215 ft / 65.5m Vertical Flow
- 1500-3000 PSI / 103-206 Bar
- 8-28 GPM / 30-106 LPM Hydraulic Flow
- 4" Male Camlock
- 28" x 15" x 17" / 71 cm x 38cm x 43cm
- AW-32 or AW-46 Hydraulic Fluid



4" DUCTILE IRON  
TWIN AGITATOR PUMP

## More Information

### Features

- Very High Flow Rates
- High Vertical Head Pressure
- Self Priming
- Run Dry Technology
- Variable Speed & Flow
- Small Portable Size
- Heavy Solids Pump
- NO Internal Friction
- NO Mechanical Seals

### Competitive Advantages

- Drill rig well cellar pumping
- Handles abrasive solids pumping applications
- Pump 20lb(9kg) per gallon(3L) oilfield slurries
- Anti-clog twin motor, double suction technology
- Lightweight dredge at 230LBS (104kg)
- Durable steel pump parts for long life
- Cost effective compared to other pumps

The Fast Flow 4" Twin Agitator Pump is made to be a survivor. All the pump's critical components are upgraded: a heat-treated ductile iron impeller, hardened 17-4 drive shaft, and stainless couplings. The two efficient hydraulic gear motors are self-lubricated by the hydraulic fluid powering the pump. There are absolutely no wear plates, no pump bearings and no mechanical seals to replace in the pump.

### Applications



- Oilfield applications
- Solids slurry pumping
- Papermill Pulp
- Black Liqour
- White Liqour
- Barge pumping
- Oil storage maintenance
- Heavy crude pumping
- Refinery tank cleaning

